

Smart Insert HT

Minimal detailing and clean lines place the Smart well in any home. Installation into an existing masonry chimney makes it perfect for replacing an inefficient open fireplace or older style insert fire. Installation into a timber framed cavity¹ can also be achieved by utilising the Smart Insert VZCC and optional fascia base rail. Fascia finished in metallic black high temperature paint.

Model	Clean air approved
Peak output	15kW
Heating area	150m ² / 3 bedroom home
Finish	Metallic black paint
Wetback	Optional Smart Booster
MfE#	102411 (DRY) / 102426 (WET)
Emission	0.49gms (DRY) / 0.82gms (WET)
Efficiency	68% (DRY) / 67% (WET)
SKU	250-0860



- 1 The Smart Insert can be installed into a timber framed cavity (false chimney) with the addition of the Smart Insert Vented Zero Clearance Cabinet (VZCC) and ECO Built-In flue kit. Visit your Metro agency or metrofires.co.nz for full details.





ECO FLUE

Maximise the performance and efficiency of your wood fire

SPECIFICATIONS

Firebox Width	Firebox Depth	Firebox Height	Flue Centre	Fascia Width	Fascia Depth	Fascia Height	Min. Floor Protector Width	Min. Floor Protector Projection	Webback In	Webback Out	Mantel Clearance
A	B	C	D	E	F	G	H	I	J	K	L
560	495	550	405	890	30	672	890	312	130	325	475
				Width		Depth		Height			
Fascia dimensions (mm)				890		30		672			



Please note: All measurements detailed above are in (mm) and do not include the 13mm insulating blanket. Specifications were correct at the time of printing but may alter and those detailed should be used only as a guide. If in doubt, please consult your local Metro Fires agency or visit metrofires.co.nz.